Miami, FL (Main) Tel: (305) 885-4992 Fax: (305) 885-9537 sales@usairmotivegse.com Los Angeles, CA

Tel: (310) 327-8407 Fax: (310) 327-8439 paula@usairmotivegse.com www.usairmotivegse.com

LIGHTWEIGHT PCA HOSE ADAPTERS



The pre-conditioned air (PCA) hose adapters everyone's raving about!

- · High density polyethylene construction
- Locks securely into place, can't shake loose
- · Weighs less than 9 pounds
- Withstands extreme heat and cold
- Corrosion, chemical and UV resistant



AIRCRAFT FUEL CELL MAINTENANCE COMMUNICATION AND ALARM SYSTEM

Safety in Communication (R)


100% instrinsically safe communication system

INTRINSIC SAFE APPROVALS

USA: Factory Mutual (FM) Class I, II, and III, Division 1, Groups A, B, C, D, E, F, & G

Europe: CENELEC - LCIE SYST 94.C 6035 X

Canada: CSA for Class I, Groups A, B, C, & D; Class II Groups G and Coal Dust; Class III



LAY-FLAT (PCA) HOSE FOR COOLING AND HEATING

An air conditioning duct that is easy to store, flexible and adjustable (wireless construction allows for reel or folded storage). Our Flat Duct is insulated and constructed in a manner that allows a 25' duct to become any length you desire in just seconds. The length is up to you. Zippers and velcro are included on each end to permit easy coupling of additional sections. Even though our hose has no wire reinforcement, it does have abrasive resistant wear strips that are sewn on to reduce wear caused by dragging across abrasive surfaces.



Temperature Range: -40° F to +250° F

Inside Diameter: 12" and 14"

Color: Duct - Yellow / Weatherstrip - Black

Length: 25' standard - other sizes available



ADDITIONAL PRODUCTS AVAILABLE: CONSUMABLES

Adhesives • Coatings & Primers • Greases • Oil and Hydraulic Fluids Chemicals • Composites • Lubricants/Fluids • Wire & Cable Solvents • Cleaners • And much, much more!